



## Banana Pi Camera module





## Shenzhen SINOVOIP CO., LIMITED Copyright Statement:

The document only describes the information about the product, however, it cannot guarantee the product function and performance. If the document content or the product feature and technical specifications included in the document are changed, it will be notified further.

Content in the document might be outdated. Our cooperation cannot promise to update this information.

Some information in the document might be disabled in your local area, including product and service. You can consult with the contact and agency in your local area.

Copyright in the document belongs to Shenzhen SINOVOIP CO., LIMITED. Users can only use the content after they have obtained authorization from our company or other obligees. However, users cannot copy, paraphrase, or create similar devices or products.

The final right to interpret and use the document belongs to Shenzhen SINOVOIP CO., LIMITED.

### More information:

Get more product and support information, please contact Shenzhen SINOVOIP CO., LIMITED ([www.banana-pi.com](http://www.banana-pi.com))

### Attention:

Due to technical requirements of the components, please do not touch directly connected

components. The core board and development system contain static-sensitive devices. Quiet electrical charges easily accumulate in the human body and the device cannot detect possible damage to equipment. It is recommended to take anti-static measures. It is recommended not to touch, store, or use anti-static effect devices.





### Product Specification:

High definition camera module for Banana Pi board via the CSI connector designed specifically for interfacing to cameras. Provide high sensitivity, low crosstalk and low noise image capture in a small and lightweight design.

### Specifications

Image sensor	Omnivision 5640 CMOS image sensor in a auto-fouces modules with integral IR filter (650±10nm)
Still resolution	5 Megapixels
Active array size	2592×1944
Max frame rate	1080P 30fps@24Mhz
Picture formats	JPEG PNG YUV420 RGB888
Video formats	Raw h.264
Connection to Banana Pi	40 Pin FPC to the Camera Sensor Interface(CSI-0)
Image control functions	Automatic exposure control (AEC) Automatic white balance(AWB) Automatic black level calibration(ABLC) Automatic band filter Mirror and flip
Temp range	Operating: -30°C to 70°C Stable Image: 0°C to 50°C
Lens size	1/4"
Dimension	36×32×10mm
Weight	8g

### Banana pi CSI Camera Connector

The CSI Camera Connector is a 40-pin FPC connector which can connect external camera module with proper signal pin mappings. The pin definitions of the CSI interface are shown as below. This is marked on the Banana Pi board as "CON1".

CSI Pin	Pin Name	GPIO
CON1 P01	LINEINL	
CON1 P02	LINEINR	
CON1 P03	VCC-CSI	



## Banana PI Camera module Hardware Manual

CON1 P04	ADC_X1	
CON1 P05	GND	
CON1 P06	ADC_X2	
CON1 P07	FMINL	
CON1 P08	ADC_Y1	
CON1 P09	FMINR	
CON1 P10	ADC_Y2	
CON1 P11	GND	
CON1 P12	CSI-FLASH	PH17
CON1 P13	LRADC0	
CON1 P14	TWI1-SDA	PB19
CON1 P15	LRADC1	
CON1 P16	TWI1-SCK	PB18
CON1 P17	CSI-D0	PE4
CON1 P18	CSI0-STBY-EN	PH19
CON1 P19	CSI0-D1	PE5
CON1 P20	CSI-PCLK	PE0
CON1 P21	CSI-D2	PE6
CON1 P22	CSI0-PWR-EN	PH16
CON1 P23	CSI-D3	PE7
CON1 P24	CSI0-MCLK	PE1
CON1 P25	CSI-D4	PE8
CON1 P26	CSI0-RESET#	PH14
CON1 P27	CSI-D5	PE9
CON1 P28	CSI-VSYNC	PE3
CON1 P29	CSI-D6	PE10
CON1 P30	CSI-HSYNC	PE2
CON1 P31	CSI-D7	PE11
CON1 P32	CSI1-STBY-EN	PH18
CON1 P33	RESET#	
CON1 P34	CSI1-RESET#	PH13
CON1 P35	CSI-IO0	PH11
CON1 P36	HPR	
CON1 P37	HPL	
CON1 P38	IPSOUT	
CON1 P39	GND	
CON1 P40	IPSOUT	